# UNITED RAILWAYS COMPANY

## TIME TABLE No. 38

TO TAKE EFFECT AT TWELVE-ONE (12:01) O'CLOCK A. M. PACIFIC TIME

### TUESDAY, AUGUST 25, 1931

SUPERSEDING TIME TABLE NO. 37 AND ALL SUPPLEMENTS THERETO
THIS TIME TABLE IS FOR THE USE OF EMPLOYES ONLY

G. E. VOTAW, Superintendent

B. L. SPERRY, Supt. Car Service

A. J. DAVIDSON, General Manager

2 WESTWARD					EASTWARD
	SECOND CLASS	Time Table No. 38		SECOND CLASS	
	61 c	Car AUGUST 25, 1931	Telephone	62 64	
		AUGUST 25, 1931	rom nty L. Table & See & See	Mixed Mixed	
	Leave Daily Ex. Sun. Sid- ings	other Trks.	Distance from County Line Safeter Mater, Wyee, Fuel & Scales.	Arrive Mon., Wed., Thur., Sat. Tue., Fri.	
	7.46M	0.0LINNTON	51.6 P J'c't.	2.117 2.117	
	7.54	3.7RIVER JUNCTION	47.9 P J'c't.	2.01 2.01	
	t 7.56 7	4.4BURLINGTON	47.2	1 1.56 1 1.56	
	8.02	86 6.6 \$TUNNEL SPUE	45.0 P	1.49 1.49	
	t 8.06	84 8.2 S BOCKTON	43.4 P	t 1.42 f 1.42	
	f 8.10	1.5	41.9 P J'c't.	t 1.35 t 1.35	
	s 8.22 51	17 14.6NORTH PLAINS	37.0 D W 1500' East	1.23 s 1.23	
	f 8.28	28 17.0 SHERMAN		t 1.16 t 1.16	
			The state of the s	1.10 112:18	
	s 8.36 34	14 20.2BANKS		1.05 12.05PM	
		5 24.5MANNING		f12.55 f11.55	
	f 9.11 34	31.4TOPHILL		f12.33 f11.33	
		4.2		112.20 111.20	
	s 9.45AM Yard	rd 41.2VERNONIAVN		12.01PM 11.00AM	
2. 2.	35	46.7ZAN			
	Yard	rd 49.7 KEASEY			
		51.6COUNTY LINE	0.0		
	Arrive Daily	W - 2 2 2 2 4 2 4		Leave Mon., Wed., Thur., Sat.	
				MANAGE TICULAT TOWN Date .	

EASTWARD TRAINS ARE SUPERIOR TO WESTWARD TRAINS OF THE SAME CLASS. EXCEPTION-No. 61 is superior to No. 62 and No. 64.

SUPERSEDING TIME TABLE NO. ST AND ALL SUPPLEMENTS THERETO

### Gales Creek and Wilson River Railroad Co.

WE	STWARD	)				E	ARD	ARD			
SECOND FIRS	T CLASS			Time Table No. 38		5.03	FIRST	SECOND			
		Car Capacity	Distance from Wilkesboro	STATIONS	Distance from Glenwood	Telephone Stations "J" Indicates Jack-box	Water, Wyes, Turn Tables, Fuel & Scales				
		S17	0.0	WILKESBORO	12.8	D					
		27	1.1	PENGRA	11.7						
		2	4.1	MENKE SPUR	8.7			7 7307			
		7	6.6	OECHARD DALE	6.2						
		80	8.9	WASHBURN	3.9	P	W. C.				
		3	11.6	GRAY'S SPUR	1.2						
		38	12.8	GLENWOOD	0.0	P	COFFEE	OL BE			
					ingli						
						attendants.	· half		100,000		
				Time Over District Average Speed per Hour	DZIU I	TVAND	60				

### EASTWARD TRAINS ARE SUPERIOR TO WESTWARD TRAINS OF THE SAME CLASS

- S. P. OVERHEAD CROSSING—Log trains must not cross overhead crossing just west of Wilkesboro when S. P. trains are passing underneath. If S. P. train is passing or approaching, log trains must come to a stop and wait until S. P. train has cleared the crossing.
- **DERAIL**—Point derail in main line 200 feet west of Cole Logging Co.'s Crossing at Gray's Spur must be left in derail position.
- YARD LIMITS—Gray's Spur: from yard sign 1500 feet east of Gray's Spur Switch to end of track, Glenwood.
- SPEED RESTRICTIONS—Speed of all trains must not exceed 12 miles per hour between Wilkesboro and Glenwood.
- GENERAL—Trainmen handling logs on disconnected trucks will be required to ride out on loaded trains, for the purpose of controlling train, over district between Glenwood and Washburn, and between M. P. 6 and M. P. 3.

	CLE	ARAN	CE TA	BLE								
* *		Heights Above Top of Rail										
	1' Wide	2' Wide	3' Wide	4' Wide	5' Wide	6' Wide	7' Wide	8' Wide	9' Wide	10' Wide		
Linnton to Keasey	19'0"	10'0"	19'0"	19'0"	19'0"	18'6"	18'3"	18'0"	17'6"	17′0″		
Front and Glisan Sts., Portland	17'	17'	17'	17'	17'	17'	17'	17'	17'	17'		
G. C. & W. R-Wilkesboro to Glenwood.	19'	19'	19'	19'	19'	18'6"	18'3"	18′	17'6"	17'		

Conductors must be absolutely positive that loads do not exceed these dimensions and must not move cars of greater dimensions without instructions from Superintendent.

### SPECIAL RULES

o. 1. Registering Stations-Linnton, River Junction, Wilkesboro, Vernonia and Keasey.

No. 2 Standard Clock and Bulletin Board located at Vernonia.

No. 3 Trap Doors must be kept down and side vestibule doors closed while trains are in motion. It is just as imperative that trap doors be down as it is that side vestibule doors be kept closed. Vestibule doors will be opened and trap doors up only when trains are making station stops.

No. 4 Derail Switches are located on all Passing Tracks and Spurs where there is danger of cars running out. Derails must be left at derail at all times, except when in use.

Point derail in passing track at Tophill is located 131 feet west of east switch. This derail must be placed in open or derail position when cars are left on passing track. When passing track is clear of cars, derail will be left in closed position.

No. 5. Automatic Block Signals. All train movements through Cornelius Tunnel will be governed by automatic block signals. Vertical position of semaphore blade, and display of green light by night, indicates that block is clear and trains may proceed. Horizontal, or inclined position of the arm, and display of red light by night, indicates that block is occupied, and trains finding semaphore in this position will come to full stop and immediately protect by flag. If block signal is found at stop position. Dispatcher will be immediately notified by telephone. No train or engine, will be permitted to go through tunnel block, when block signals are in stop position without flagman preceding train entirely through tunnel. Fifteen (15) minutes should be allowed flagman in order to insure full protection before starting train and then train should not exceed a speed of five (5) miles per hour. No flag movement will be made through tunnel unless authorized by Train Dispatcher, except, if impossible to get in communication with Train Dispatcher flag movement will be made as outlined above.

Automatic signal known as "stop signal" legated 1000 feet west of Topkill tunnel governs the movement of eactward trains

Automatic signal, known as "stop signal," located 1000 feet west of Tophill tunnel, governs the movement of eastward trains. When trains are stopped by signal in stop position they will be governed by rule 509.

No. 6. Rule 83-A will not apply at initial Stations which are not Telegraph Stations nor at Telegraph Stations except during office hours, or when an Operator is on duty after office hours.

No. 7. At Junction Switch with S. P. & S., Linnton, eastward trains, will comply with rule 83 by obtaining check on all overdue trains, from train Dispatcher by telephone.

No. 8. At Wilkesboro, when office is open, all trains will register by ticket, form 1060, as per rule 83-B and will require from operator a check of register on form 1211.

No. 9. Normal position of Junction Switch, Wilkesboro, will be for the United Rys. Main line.

No. 10. Railroad Crossings located as follows: S. P. Co. (McFarlane Bros. Mill) 4.2 miles west of Banks. All trains will come to full stop at this crossing and not proceed until way is known to be clear.

### SPEED RESTRICTIONS

No. 11. Passenger Trains must not exceed thirty (30) miles per hour, freight trains twenty-five (25) miles per hour between Linnton and Wilkesboro, and twenty (20) miles per hour between Wilkesboro and Keasey. Trains handling logs on disconnected trucks must not exceed twelve (12) miles per hour and trains handling logs on flat cars must not exceed twenty (20) miles per hour over any portion of the railway. Trains must reduce speed to twelve (12) miles per hour over all bridges between Linnton and Cornelius tunnel. Eastward freight trains will use not less than thirty-five (35) minutes between Tophill and Manning. Locomotives backing up must not exceed speed of twenty (20) miles per hour.

### YARDS

No. 12. Linnton Yard Limits extend from Yard Sign one mile east of Linnton depot to Yard Sign 600 feet west of the West Oregon Lumber Company Switch on Portland Division and Yard Sign 500 feet west of Junction Switch on United Rys.

Wilkesboro Yard Limits, from Yard Sign 2000 feet east of Junction Switch to Yard Sign 2000 feet west of Junction Switch, and to Yard Sign 500 feet west of west switch Pengra passing track on G. C. & W. R. Ry.

Braun, from Yard Sign 500 feet east of East passing track switch to Yard Sign 1000 feet west of West passing track Switch.

Connacher, from Yard Sign 500 feet east of Switch to Connacher track No. 1 to Yard Sign 1500 feet west of Switch to Connacher track No. 2.

McPherson, from Yard Sign 2000 feet east of McPherson Spur No. 1 to Yard Sign 2000 feet west of McPherson Spur No. 2. Vernonia, from Yard Sign 2640 feet west of West passing track Switch to Yard Sign 2200 feet east of East Switch of Storage Track. Keasey, from Yard Sign 2640 feet east of East Switch to Yard Sign 1000 feet west of Eastman Spur.

### GENERAL

- No. 13. All trainmen and others interested are hereby warned that the majority of cattle guards on United Railways Company are closer to tracks than required standard of the Public Service Commission of Oregon.
- No. 14. Sign reading "Impaired Clearance" placed upon switch stand at entrance of spur or siding indicates—there are platforms or structures located alongside same which do not provide minimum horizontal clearance prescribed by Public Service Commission of Oregon. Employees will use care and avoid risk of injury while working on spurs or sidings protected with "Impaired Clearance" signs.

No. 15. The double heading of trains between Keasey and Tophill is prohibited. Trains handling logs on disconnected trucks must not under any circumstances be double headed between Keasey and Rafton.

No. 16. When engines and cabooses equipped with adjustable couplers are being moved, the Federal Law prohibits the handling in one train of equipment including engines and cabooses unless couplers are all in either the high or the low position. This includes couplers on engines and on cabooses on the opposite ends from those in service. When it is necessary to change position of adjustable couplers, there must be no failure to again connect chain between cutting lever and pin lifter so that cutting lever will be operative.

### LOG TRAIN SERVICE

No. 17. Following restrictions must be observed in the handling of logs loaded on disconnected trucks:

Loads must not exceed eleven (11) feet in width and must not exceed eighty (80) feet in length, except when special permits are issued authorizing Conductors to move loads exceeding eighty (80) feet in length.

The load limit for 80,000 capacity trucks will be 12,000 feet; load limit for 100,000 capacity trucks will be 14,000 feet.

There must be a clearance of not less than twelve (12) inches from the top of rail to the bottom of logs.

In event of stalling on grade, Enginemen must not take slack in attempting to start, as to do so may result in pulling trucks from under loads.

Conductors will decline to handle in trains loads of logs which do not conform to the above restrictions.

No. 18. Trainmen handling logs on disconnected trucks will be required to Ride Out on loaded trains for the purpose of controlling train over district between Keasey and Zan, Tophill and Manning and Rockton and Rafton.

Trainmen handling empty trucks when provided with a caboose on the rear will not be required to Ride Out, but in every case there must be not less than two trainmen in caboose over district mentioned above. Trainmen when not provided with a caboose will be required to Ride Out over the entire division when handling empty trucks.

No. 19. Trainmen in log service when handling logs on disconnected trucks will be required, when on duty, to wear shoes properly equipped with caulks.

### Commercial Spurs and Passenger Flag Stops Between Stations

Commercial by	dis and ra	sport or Line	g brobs ber	ween stations
Name	Miles from Linnton	Capacity of Sidings in Cars	Switch at	Flag Stop for Trains
Armona	2.1			All Trains
Lucerne	2.4			All Trains
Petty	3.6	S 9	West End	All Trains
Falkenberg	6.1	S 2	West End	All Trains
McCoy	7.0			All Trains
Culliton	8.6	S 10	West End	Not Pass. Stop
Valle Vista	8.9			All Trains
Helvetia	10.3	S 6	East End	All Trains
Groveland	10.9			All Trains
Connell	11.8	87	West End	All Trains
Twinfir	12.2	1	East End	All Trains
Lincoln	12.8	S 7	East End	All Trains
Vadis	15.8	9 13	East End Double End	All Trains
Grove Lumber Co	15.9	6	East End	Not Pass. Stop
Dersham	16.4			All Trains
Christie	16.1	S 12	East End	All Trains
Davies	22.0			All Trains
The Vernonia Co	22.7	4	East End	All Trains
Carstens	24.0			All Trains
Buxton	27.3			All Trains
Elwood Lbr. Co. Spur	27.4	S 12	West End	Not Pass. Stop
Outfit Spur	32.0	S 9	West End	Not Pass. Stop
Schmidlin Spur	34.2	S 4	East End	All Trains
Connacher Spur	35.9	Log Spur	West End	All Trains
McPherson No. 1	39.1	Log Spur	East End	All Trains
McPherson No. 2.	39.1	Log Spur	West End	All Trains
Trehorn	30.14	S 3	East End	All Trains
Poynter	4.3	Log Spur	East End	All Trains
Homewood	45.9			All Trains
Early	47.5			All Trains
Tara	47.8	S 4	East End	All Trains
Lausman	48.4			All Trains
Eastman	51.1	Log Spur	West End	Not Pass. Stop
THE RESERVE TO SHARE THE PARTY OF THE PARTY	THE RESERVE AND ADDRESS OF THE PERSON NAMED IN COLUMN 1			

Tonnage Rating of Engine
--------------------------

1		Will Land					Cl	ass of Eng	gine		The same			
		Ruling	GC&WR	N1 N3	N2	N4 N5	N6	N7	F1	D2	D3	D4	D5	D6
	District	Grade	1 & 2	350-352 & 370	355- 364	300-305 315	325- 326	335- 337	450- 484	150- 151	152-157 158	153-154 155	156	159
	Linnton to Wilkesboro	1.5	532	638	800	756	812	800	762	467	537	545	394	579
	Wilkesboro to Linnton	1.2	762	904	1200	1022	1218	1200	1145	722	816	812	599	871
	Wilkesboro to Keasey	2.3	293	357	445	423	450	445	414	236	284	301	208	319
	Keasey to Wilkesboro	1.5	532	638	800	756	812	800	762	467	537	545	394	579

### Footage Rating for Engines in Logging Service

Keasey to Wilkesboro	1.5	114000′	135000′	172000′	160000′	174000′	172000′	164000′	100000′	114000′	117000′	85000′	124000′	
Wilkesboro to Rafton	1.0	165,000 feet	200,000 feet	240,000 feet	232,000 feet	251,000 feet	240,000 feet	229,000 feet	144,400 feet	163,200 feet	162,400 feet	119,800 feet	174,000 feet	

### LOCATION AND LENGTH OF TUNNELS

No.	Location	Length
1	7.6 miles west of Linnton	4180 feet
2	Tophill	

### COMPANY SURGEONS

Dr. Chas. Newcastle, Chief Surgeon	Portland
Dr. Wilmot C. Foster, Asst. Surgeon	Portland
Dr. C. E. Brous.	Linnton
Dr. Marvin R. Eby	Vernonia

### STRETCHERS

Located at

VERNONIA.....STATION

### WATCH INSPECTORS

A. L. Haman, Chief Time InspectorSt. Paul, Minn.
W. H. Saxton, 245 Washington St Portland, Ore.
Dillen Rogers, Killingsworth and Albina Avenues
Portland, Ore
A I Vullandan Vannania One

L. H. JAMES, Dispatcher. F. S. BARLOW, Dispatcher. L. S. NELSON, Dispatcher.

E. M. HERRING, Asst. Chief Dispatcher. E. B. ARTHUR, Asst. Chief Dispatcher. R. C. SCOFFERN, Chief Dispatcher. E. B. HEATH, Trainmaster.